

APPENDIX II - EPA REQUIRED DATA

Details compliance with requirements of 40CFR58 §58.10 and Appendices A, C, D, and E

Required General Information on Monitoring Network

| Pollutant | MSA | MSA Pop.* | 2010 Maximum Design Values | #Monitors Required | #Monitors Operating** |
|-------------------|-------------------|-----------|---|--------------------|-----------------------|
| Carbon Monoxide | 6200 Phoenix-Mesa | 3,954,598 | 1-Hour: 9.0 ppm 8-Hour: 3.3 ppm | 0 | 12 |
| Ozone | 6200 Phoenix-Mesa | 3,954,598 | 1-hour: 0.079 ppm | 2 | 17 |
| Nitrogen Dioxide | 6200 Phoenix-Mesa | 3,954,598 | 1-hour: 0.0790 ppm Annual: 0.0245 ppm | 0 | 5 |
| PM _{2.5} | 6200 Phoenix-Mesa | 3,954,598 | 24-hour: 24.3 µg/m ³ Annual: 10.2 µg/m ³ | 3 | 4 |
| PM ₁₀ | 6200 Phoenix-Mesa | 3,954,598 | 24-hour: 279 µg/m ³ Estimated Exceedances: 1 | 6-10 | 16 |
| Sulfur Dioxide | 6200 Phoenix-Mesa | 3,954,598 | 24-hour: 0.0054 ppm Annual: 0.00174 ppm | 0 | 2 |

*Based on the 2008 United States Census population estimate.

**Only includes monitors operated by the Maricopa County Air Quality Department; does not include monitors operated by other agencies within the MSA.

Required General Statement Regarding Changes to the PM_{2.5} Network

In the event the department needed to move or change a violating PM_{2.5} monitor the following procedure would be followed: The department would hold a public hearing regarding the requested change. Details and documentation of the requested change, as well as all public comments, would then be forwarded to the EPA for approval. Any action on the department's part will be dependent on EPA approval.

Please note that the previous statement is general in nature and is required to be placed in the annual network review by 40CFR58. The department does not currently have any violating PM_{2.5} monitors, nor does it have any proposals to move any PM_{2.5} monitors.

Notes regarding appendix data

Analysis Method (filters only) refers to the method used to process filter-based particulate samples.

Distance from Supporting Structure refers to those sample probes that are attached to a supporting structure, such as the side of a building. In most cases the sample probe is located above the supporting structure, in which case the entry will say N/A.

Distance from Obstructions refers to those obstructions, both on the roof and off the roof, which are located higher than the probe. In the case of a nearby obstruction being higher than the probe, details of its location will be listed in the entry. If there are no obstructions higher than the probe, then the entry will be N/A.

Last Annual Performance Evaluation Date refers to the performance evaluations detailed in 40CFR58, Appendix A, §3.2.2. These performance evaluations are performed by an agency outside of MCAQD. At least 25% of the network should be evaluated once per calendar quarter.

Last Two Semi-Annual Flow Rate Audit Dates refers to the performance evaluations detailed in 40CFR58, Appendix A, §3.2.4. These performance evaluations are performed by an agency outside of MCAQD at least once every six months.

Probe Sample Line Material refers to the material makeup of the intake sample lines.

Pollutant Sample Residence Time refers to the amount of time that it takes a sample of air to travel between the probe inlet and the monitor. This residence time is calculated by a formula that is based on the sample line diameter and length and the flow rate of the air intake. It is important to keep this residence time low so as to prevent gases in the air sample from reacting with the sample line material or with other gases in the sample; e.g. ozone could react with nitrogen oxide in the air sample if the residence time exceeds 20 seconds. This measurement only applies to NO₂, SO₂, and O₃ monitors.

BLUE POINT

County ID: BP

AQS ID: 04-013-9702

Address: Bush Highway & Usery Pass Road, Maricopa County

Coordinates: 33.54549N – 111.60925W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | |
|--|-------------------------|
| Pollutant/Monitor Type | Ozone |
| Sampling Schedule | Continuous |
| Analysis Method (filters only) | N/A |
| Any Proposal to Remove or Move Monitor? | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A |
| -Appendix A Requirements | |
| # Precision Checks Performed Annually | 27 |
| # Accuracy Checks Performed Annually | 6 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly |
| Frequency of Flow Rate Verification | N/A |
| -Appendix C Requirements | |
| Sampler Make & Model | API M400 |
| Date Established | 01/01/1993 |
| Classification | SLAMS |
| Method (FRM, FEM, ARM) | FEM |
| -Appendix D Requirements | |
| Monitoring Objective | Max Ozone Concentration |
| Monitoring Scale | Urban |
| Sampling Season | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes |
| -Appendix E Requirements | |
| Distance between collocated samplers | N/A |
| Probe Inlet Height | 5.3 meters |
| Airflow Arc | 360° |
| Probe Sample Line Material | Teflon |
| Pollutant Sample Residence Time | 7.6 sec |
| Distance from Supporting Structure | N/A |
| Distance from Obstructions | N/A |
| Distance to Furnace Flue | N/A |
| Spacing from Trees | N/A |
| Nearest Major Roadway | Bush Highway |
| Distance and Direction to Road | 160 meters, South |
| Traffic Count (ADT) | 1,000 |
| Groundcover | Paved |

BUCKEYE
County ID: BE
AQS ID: 04-013-4011
Address: 26449 W 100th DR, Buckeye
Coordinates: 33.37005N – 111.62070W
Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | | | | |
|--|-----------------------|-----------------------|-----------------------|-----------------------|
| Pollutant/Monitor Type | Ozone | CO | NO ₂ | PM ₁₀ |
| Sampling Schedule | Continuous | Continuous | Continuous | Continuous |
| Analysis Method (filters only) | N/A | N/A | N/A | N/A |
| Any Proposal to Remove or Move Monitor? | No | No | No | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A | N/A | N/A | N/A |
| -Appendix A Requirements | | | | |
| # Precision Checks Performed Annually | 21 | 14 | 25 | 24 |
| # Accuracy Checks Performed Annually | 5 | 1 | 7 | 2 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes | Yes | Yes | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly | Bi-Weekly | Bi-Weekly | N/A |
| Frequency of Flow Rate Verification | N/A | N/A | N/A | Bi-Weekly |
| -Appendix C Requirements | | | | |
| Sampler Make & Model | API M400 | API M300 | API M200 | Thermo TEOM 1400AB |
| Date Established | 08/01/2004 | 08/01/2004 | 08/01/2004 | 08/01/2004 |
| Classification | SLAMS | SLAMS | SLAMS | SLAMS |
| Method (FRM, FEM, ARM) | FEM | FRM | FRM | FEM |
| -Appendix D Requirements | | | | |
| Monitoring Objective | Population Exposure | Population Exposure | Source Oriented | Population Exposure |
| Monitoring Scale | Neighborhood | Neighborhood | Urban | Neighborhood |
| Sampling Season | Apr-Dec* | Sep-Mar | Jan-Dec | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes | Yes | Yes | Yes |
| -Appendix E Requirements | | | | |
| Distance between collocated samplers | N/A | N/A | N/A | N/A |
| Probe Inlet Height | 4 meters | 4 meters | 4 meters | 4.5 meters |
| Airflow Arc | 360° | 360° | 360° | 360° |
| Distance from Supporting Structure | N/A | N/A | N/A | N/A |
| Probe Sample Line Material | Teflon | Teflon | Teflon | N/A |
| Pollutant Sample Residence Time | 4.0 sec | N/A | 4.0 sec | N/A |
| Distance from Obstructions | N/A | N/A | N/A | N/A |
| Distance to Furnace Flue | N/A | N/A | N/A | N/A |
| Spacing from Trees | 14 meters, N | 14 meters, N | 14 meters, N | 14 meters, N |
| Nearest Major Roadway | US Hwy 85 | US Hwy 85 | US Hwy 85 | US Hwy 85 |
| Distance and Direction to Road | 31 meters, N | 31 meters, N | 31 meters, N | 31 meters, N |
| Traffic Count (ADT) | 3,000 | 3,000 | 3,000 | 3,000 |
| Groundcover | Paved | Paved | Paved | Paved |

*Seasonal ozone monitors have been changed to year round operation in October 2010.

CAVE CREEK

County ID: CC

AQS ID: 04-013-4008

Address: 37019 N Lava Lane, Phoenix

Coordinates: 33.82169N – 112.01739W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | |
|--|-------------------------|
| Pollutant/Monitor Type | Ozone |
| Sampling Schedule | Continuous |
| Analysis Method (filters only) | N/A |
| Any Proposal to Remove or Move Monitor? | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A |
| -Appendix A Requirements | |
| # Precision Checks Performed Annually | 19 |
| # Accuracy Checks Performed Annually | 4 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly |
| Frequency of Flow Rate Verification | N/A |
| -Appendix C Requirements | |
| Sampler Make & Model | API M400 |
| Date Established | 07/20/2001 |
| Classification | SLAMS |
| Method (FRM, FEM, ARM) | FEM |
| -Appendix D Requirements | |
| Monitoring Objective | Max Ozone Concentration |
| Monitoring Scale | Urban |
| Sampling Season | Apr-Dec* |
| Network Meets Minimum Number of Monitors Required? | Yes |
| -Appendix E Requirements | |
| Distance between collocated samplers | N/A |
| Probe Inlet Height | 4.8 meters |
| Airflow Arc | 360° |
| Probe Sample Line Material | Teflon |
| Pollutant Sample Residence Time | 10.2 sec |
| Distance from Supporting Structure | N/A |
| Distance from Obstructions | N/A |
| Distance to Furnace Flue | N/A |
| Spacing from Trees | 20 meters, E |
| Nearest Major Roadway | 32 nd Street |
| Distance and Direction to Road | 240 meters, NE |
| Traffic Count (ADT) | 1,000 |
| Groundcover | Paved |

*Seasonal ozone monitors have been changed to year round operation in October 2010.

CENTRAL PHOENIX

County ID: CP

AQS ID: 04-013-3002

Address: 1645 E Roosevelt, Phoenix

Coordinates: 33.45793N - 112.04601W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | | | | | |
|--|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| Pollutant/Monitor Type | Ozone | CO | NO ₂ | SO ₂ | PM ₁₀ |
| Sampling Schedule | Continuous | Continuous | Continuous | Continuous | Continuous |
| Analysis Method (filters only) | N/A | N/A | N/A | N/A | N/A |
| Any Proposal to Remove or Move Monitor? | No | No | No | No | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A | N/A | N/A | N/A | N/A |
| -Appendix A Requirements | | | | | |
| # Precision Checks Performed Annually | 26 | 26 | 26 | 26 | 24 |
| # Accuracy Checks Performed Annually | 5 | 4 | 4 | 6 | 2 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes | Yes | Yes | Yes | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly | Bi-Weekly | Bi-Weekly | Bi-Weekly | N/A |
| Frequency of Flow Rate Verification | N/A | N/A | N/A | N/A | Bi-Weekly |
| -Appendix C Requirements | | | | | |
| Sampler Make & Model | API M400 | API M300 | API M200 | API M100 | Thermo TEOM 1400AB |
| Date Established | 06/01/1967 | 10/01/1966 | 01/01/1967 | 01/01/1965 | 04/01/1985 |
| Classification | SLAMS | SLAMS | SLAMS | SLAMS | SLAMS |
| Method (FRM, FEM, ARM) | FEM | FRM | FRM | FEM | FEM |
| -Appendix D Requirements | | | | | |
| Monitoring Objective | Population Exposure | Population Exposure | Highest Concentration | Highest Concentration | Population Exposure |
| Monitoring Scale | Neighborhood | Neighborhood | Neighborhood | Neighborhood | Neighborhood |
| Sampling Season | Jan-Dec | Jan-Dec | Jan-Dec | Jan-Dec | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes | Yes | Yes | Yes | Yes |
| -Appendix E Requirements | | | | | |
| Distance between collocated samplers | N/A | N/A | N/A | N/A | N/A |
| Probe Inlet Height | 11.3 meters | 11.3 meters | 11.3 meters | 11.3 meters | 11.3 meters |
| Airflow Arc | 360° | 360° | 360° | 360° | 360° |
| Probe Sample Line Material | Teflon | Teflon | Teflon | Teflon | N/A |
| Pollutant Sample Residence Time | 9.0 sec | N/A | 9.0 sec | 10.0 sec | N/A |
| Distance from Supporting Structure | N/A | N/A | N/A | N/A | N/A |
| Distance from Obstructions | N/A | N/A | N/A | N/A | N/A |
| Distance to Furnace Flue | N/A | N/A | N/A | N/A | N/A |
| Spacing from Trees | N/A | N/A | N/A | N/A | N/A |
| Nearest Major Roadway A | 16 th Street | 16 th Street | 16 th Street | 16 th Street | 16 th Street |
| Distance and Direction to Road | 88 meters, W | 88 meters, W | 88 meters, W | 88 meters, W | 91 meters, W |
| Traffic Count (ADT) | 24,000 | 24,000 | 24,000 | 24,000 | 24,000 |
| Nearest Major Roadway B | Roosevelt St. | Roosevelt St. | Roosevelt St. | Roosevelt St. | Roosevelt St. |
| Distance and Direction to Road | 75 meters, N | 75 meters, N | 75 meters, N | 75 meters, N | 75 meters, N |
| Traffic Count (ADT) | Unknown | Unknown | Unknown | Unknown | Unknown |
| Groundcover | Paved | Paved | Paved | Paved | Paved |

DEER VALLEY

County ID: DV

AQS ID: 04-013-4018

Address: 1030 West Deer Valley Road, Phoenix

Coordinates: 33.684627N -112.08635W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | |
|--|---|
| Pollutant/Monitor Type | Lead |
| Sampling Schedule | 1 in 6 day |
| Analysis Method (filters only) | Filters sent out to independent laboratory for weighing |
| Any Proposal to Remove or Move Monitor? | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A |
| -Appendix A Requirements | |
| # Precision Checks Performed Annually | 46 (collocated) |
| # Accuracy Checks Performed Annually | 0* |
| All Precision/Accuracy Reports Submitted to AQS? | Yes* |
| Annual Data Certification Submitted? | Pending for July 2011 |
| Frequency of One-Point QC Check | N/A |
| Frequency of Flow Rate Verification | Semi-Annual |
| -Appendix C Requirements | |
| Sampler Make & Model | Hi-Q TSP Sampler |
| Date Established | 07/01/2010 |
| Classification | SLAMS |
| Method (FRM, FEM, ARM) | FRM |
| -Appendix D Requirements | |
| Monitoring Objective | Source Oriented |
| Monitoring Scale | Middle Scale |
| Sampling Season | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes |
| -Appendix E Requirements | |
| Distance between collocated samplers | 2.7 meters |
| Probe Inlet Height | 4.1 meters |
| Airflow Arc | 360° |
| Probe Sample Line Material | N/A |
| Pollutant Sample Residence Time | N/A |
| Distance from Supporting Structure | N/A |
| Distance from Obstructions | N/A |
| Distance to Furnace Flue | N/A |
| Spacing from Trees | N/A |
| Nearest Major Roadway | Deer Valley |
| Distance and Direction to Road | 300 meters, S |
| Traffic Count (ADT) | 6,452 |
| Groundcover | Paved |

*Calibrating instrument was damaged by manufacturer. A new calibrator was received in early 2011 and accuracy checks have been resumed.

DURANGO COMPLEX
County ID: DC
AQS ID: 04-013-9812
Address: 2702 RC Esterbrooks Blvd, Phoenix
Coordinates: 33.42650N -112.11814W
Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | | |
|--|------------------------|-------------------------|
| Pollutant/Monitor Type | PM₁₀ | PM_{2.5} |
| Sampling Schedule | Continuous | Continuous |
| Analysis Method (filters only) | N/A | N/A |
| Any Proposal to Remove or Move Monitor? | No | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A | Yes |
| -Appendix A Requirements | | |
| # Precision Checks Performed Annually | 22 | 16 |
| # Accuracy Checks Performed Annually | 2 | 1 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 | Pending for July 2011 |
| Frequency of One-Point QC Check | N/A | N/A |
| Frequency of Flow Rate Verification | Bi-Weekly | Bi-Weekly |
| -Appendix C Requirements | | |
| Sampler Make & Model | Thermo TEOM 1400AB | Thermo FDMS-TEOM 1400AB |
| Date Established | 07/01/1999 | 07/01/2005 |
| Classification | SLAMS | SLAMS |
| Method (FRM, FEM, ARM) | FEM | FEM |
| -Appendix D Requirements | | |
| Monitoring Objective | Highest Concentration | Highest Concentration |
| Monitoring Scale | Middle | Middle |
| Sampling Season | Jan-Dec | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes | Yes |
| -Appendix E Requirements | | |
| Distance between collocated samplers | N/A | N/A |
| Probe Inlet Height | 3.9 meters | 4.8 meters |
| Airflow Arc | 360° | 360° |
| Probe Sample Line Material | N/A | N/A |
| Pollutant Sample Residence Time | N/A | N/A |
| Distance from Supporting Structure | N/A | N/A |
| Distance from Obstructions | N/A | N/A |
| Distance to Furnace Flue | N/A | N/A |
| Spacing from Trees | 14 meters, S | 14 meters, S |
| Nearest Major Roadway | 27 th Ave | 27 th Ave |
| Distance and Direction to Road | 78 meters, E | 76 meters, E |
| Traffic Count (ADT) | 16,000 | 16,000 |
| Groundcover | Paved | Paved |

DYSART

County ID: DY

AQS ID: 04-013-4010

Address: 16825 N Dysart Rd, Surprise

Coordinates: 33.63713N – 112.34184W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | | | |
|--|-----------------------|-----------------------|------------------------|
| Pollutant/Monitor Type | Ozone | CO | PM₁₀ |
| Sampling Schedule | Continuous | Continuous | Continuous |
| Analysis Method (filters only) | N/A | N/A | N/A |
| Any Proposal to Remove or Move Monitor? | No | No | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A | N/A | N/A |
| -Appendix A Requirements | | | |
| # Precision Checks Performed Annually | 18 | 12 | 24 |
| # Accuracy Checks Performed Annually | 3 | 3 | 2 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes | Yes | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly | Bi-Weekly | N/A |
| Frequency of Flow Rate Verification | N/A | N/A | Monthly |
| -Appendix C Requirements | | | |
| Sampler Make & Model | API M400 | API M300 | Thermo TEOM 1400AB |
| Date Established | 7/21/2003 | 09/01/2003 | 07/14/2003 |
| Classification | SLAMS | SLAMS | SLAMS |
| Method (FRM, FEM, ARM) | FEM | FRM | FRM |
| -Appendix D Requirements | | | |
| Monitoring Objective | Population Exposure | Population Exposure | Population Exposure |
| Monitoring Scale | Neighborhood | Neighborhood | Neighborhood |
| Sampling Season | Apr-Dec* | Sep-Mar | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes | Yes | Yes |
| -Appendix E Requirements | | | |
| Distance between collocated samplers | N/A | N/A | N/A |
| Probe Inlet Height | 3.3 meters | 3.3 meters | 2.6 meters |
| Airflow Arc | 360° | 360° | 360° |
| Probe Sample Line Material | Teflon | Teflon | N/A |
| Pollutant Sample Residence Time | 4.8 sec | N/A | N/A |
| Distance from Supporting Structure | N/A | N/A | N/A |
| Distance from Obstructions | N/A | N/A | N/A |
| Distance to Furnace Flue | N/A | N/A | N/A |
| Spacing from Trees | N/A | N/A | N/A |
| Nearest Major Roadway A | Dysart | Dysart | Dysart |
| Distance and Direction to Road | 17 meters, W | 17 meters, W | 12 meters, W |
| Traffic Count (ADT) | 12,000 | 12,000 | 12,000 |
| Nearest Major Roadway B | Bell Rd | Bell Rd | Bell Rd |
| Distance and Direction to Road | 495 meters, N | 495 meters, N | 460 meters, N |
| Traffic Count (ADT) | 43,000 | 43,000 | 43,000 |
| Groundcover | Paved/Gravel | Paved/Gravel | Paved/Gravel |

*Seasonal ozone monitors have been changed to year round operation in October 2010.

FALCON FIELD

County ID: FF

AQS ID: 04-013-1010

Address: 4530 E McKellips Rd, Mesa

Coordinates: 33.45223N – 111.73331W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | |
|--|-----------------------|
| Pollutant/Monitor Type | Ozone |
| Sampling Schedule | Continuous |
| Analysis Method (filters only) | N/A |
| Any Proposal to Remove or Move Monitor? | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A |
| -Appendix A Requirements | |
| # Precision Checks Performed Annually | 23 |
| # Accuracy Checks Performed Annually | 4 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly |
| Frequency of Flow Rate Verification | N/A |
| -Appendix C Requirements | |
| Sampler Make & Model | API M400 |
| Date Established | 06/01/1989 |
| Classification | SLAMS |
| Method (FRM, FEM, ARM) | FEM |
| -Appendix D Requirements | |
| Monitoring Objective | Population Exposure |
| Monitoring Scale | Neighborhood |
| Sampling Season | Apr-Dec* |
| Network Meets Minimum Number of Monitors Required? | Yes |
| -Appendix E Requirements | |
| Distance between collocated samplers | N/A |
| Probe Inlet Height | 9.3 meters |
| Airflow Arc | 360° |
| Probe Sample Line Material | Teflon |
| Pollutant Sample Residence Time | 16.4 sec |
| Distance from Supporting Structure | N/A |
| Distance from Obstructions | N/A |
| Distance to Furnace Flue | N/A |
| Spacing from Trees | N/A |
| Nearest Major Roadway | McKellips |
| Distance and Direction to Road | 58 meters, S |
| Traffic Count (ADT) | 29,000 |
| Groundcover | Paved |

*Seasonal ozone monitors have been changed to year round operation in October 2010.

FOUNTAIN HILLS

County ID: FH

AQS ID: 04-013-9704

Address: 16426 E Palisades Blvd, Fountain Hills

Coordinates: 33.61103N – 111.72529W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | |
|--|---|
| Pollutant/Monitor Type | Ozone |
| Sampling Schedule | Continuous |
| Analysis Method (filters only) | N/A |
| Any Proposal to Remove or Move Monitor? | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A |
| -Appendix A Requirements | |
| # Precision Checks Performed Annually | 22 |
| # Accuracy Checks Performed Annually | 5 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly |
| Frequency of Flow Rate Verification | N/A |
| -Appendix C Requirements | |
| Sampler Make & Model | API M400 |
| Date Established | 04/01/1996 |
| Classification | SLAMS |
| Method (FRM, FEM, ARM) | FEM |
| -Appendix D Requirements | |
| Monitoring Objective | Max Ozone Concentration |
| Monitoring Scale | Neighborhood |
| Sampling Season | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes |
| -Appendix E Requirements | |
| Distance between collocated samplers | N/A |
| Probe Inlet Height | 4.3 meters |
| Airflow Arc | 360° |
| Probe Sample Line Material | Teflon |
| Pollutant Sample Residence Time | 4.8 sec |
| Distance from Supporting Structure | N/A |
| Distance from Obstructions | Canopy 1 meter higher than probe, located 9 meters to the south |
| Distance to Furnace Flue | N/A |
| Spacing from Trees | 15 meters, W |
| Nearest Major Roadway | Palisades Blvd |
| Distance and Direction to Road | 70 meters, SW |
| Traffic Count (ADT) | 8,000 |
| Groundcover | Paved |

GLENDALE
County ID: GL
AQS ID: 04-013-2001
Address: 6001 W Olive, Glendale
Coordinates: 33.56936N – 112.19153W
Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | | | |
|--|-----------------------|-----------------------|------------------------|
| Pollutant/Monitor Type | Ozone | CO | PM₁₀ |
| Sampling Schedule | Continuous | Continuous | Continuous |
| Analysis Method (filters only) | N/A | N/A | N/A |
| Any Proposal to Remove or Move Monitor? | No | No | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A | N/A | N/A |
| -Appendix A Requirements | | | |
| # Precision Checks Performed Annually | 19 | 13 | 24 |
| # Accuracy Checks Performed Annually | 3 | 2 | 2 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes | Yes | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly | Bi-Weekly | N/A |
| Frequency of Flow Rate Verification | N/A | N/A | Monthly |
| -Appendix C Requirements | | | |
| Sampler Make & Model | API M400 | API M300 | Thermo TEOM 1400AB |
| Date Established | 01/01/1974 | 01/01/1974 | 07/01/1987 |
| Classification | SLAMS | SLAMS | SLAMS |
| Method (FRM, FEM, ARM) | FEM | FRM | FRM |
| -Appendix D Requirements | | | |
| Monitoring Objective | Population Exposure | Population Exposure | Population Exposure |
| Monitoring Scale | Neighborhood | Neighborhood | Neighborhood |
| Sampling Season | Apr-Dec* | Sep-Mar | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes | Yes | Yes |
| -Appendix E Requirements | | | |
| Distance between collocated samplers | N/A | N/A | N/A |
| Probe Inlet Height | 6.0 meters | 6.0 meters | 7.4 meters |
| Airflow Arc | 360° | 360° | 360° |
| Probe Sample Line Material | Teflon | Teflon | N/A |
| Pollutant Sample Residence Time | 15.5 sec | N/A | N/A |
| Distance from Supporting Structure | N/A | N/A | N/A |
| Distance from Obstructions | N/A | N/A | N/A |
| Distance to Furnace Flue | N/A | N/A | N/A |
| Spacing from Trees | N/A | N/A | N/A |
| Nearest Major Roadway A | Olive Ave | Olive Ave | Olive Ave |
| Distance and Direction to Road | 225 meters, S | 225 meters, S | 227 meters, S |
| Traffic Count (ADT) | 25,000 | 25,000 | 25,000 |
| Nearest Major Roadway B | 59 th Ave | 59 th Ave | 59 th Ave |
| Distance and Direction to Road | 475 meters, E | 475 meters, E | 430 meters, E |
| Traffic Count (ADT) | 30,500 | 30,500 | 30,500 |
| Groundcover | Paved | Paved | Paved |

*Seasonal ozone monitors have been changed to year round operation in October 2010.

GREENWOOD

County ID: GR

AQS ID: 04-013-3010

Address: 1128 N 27th Ave., Phoenix

Coordinates: 33.46093N – 112.11748W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | | | |
|--|-----------------------|-----------------------|------------------------|
| Pollutant/Monitor Type | CO | NO₂ | PM₁₀ |
| Sampling Schedule | Continuous | Continuous | Continuous |
| Analysis Method (filters only) | N/A | N/A | N/A |
| Any Proposal to Remove or Move Monitor? | No | No | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A | N/A | N/A |
| -Appendix A Requirements | | | |
| # Precision Checks Performed Annually | 26 | 28 | 24 |
| # Accuracy Checks Performed Annually | 3 | 5 | 2 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes | Yes | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly | Bi-Weekly | N/A |
| Frequency of Flow Rate Verification | N/A | N/A | Bi-Weekly |
| -Appendix C Requirements | | | |
| Sampler Make & Model | API M300 | API M200 | Thermo TEOM 1400AB |
| Date Established | 11/01/1993 | 11/01/1993 | 11/01/1993 |
| Classification | SLAMS | SLAMS | SLAMS |
| Method (FRM, FEM, ARM) | FRM | FRM | FEM |
| -Appendix D Requirements | | | |
| Monitoring Objective | Population Exposure | Population Exposure | Population Exposure |
| Monitoring Scale | Middle | Middle | Middle |
| Sampling Season | Jan-Dec | Jan-Dec | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes | Yes | Yes |
| -Appendix E Requirements | | | |
| Distance between collocated samplers | N/A | N/A | N/A |
| Probe Inlet Height | 4.2 meters | 4.2 meters | 4.4 meters |
| Airflow Arc | 360° | 360° | 360° |
| Probe Sample Line Material | Teflon | Teflon | N/A |
| Pollutant Sample Residence Time | N/A | 4.3 sec | N/A |
| Distance from Supporting Structure | N/A | N/A | N/A |
| Distance from Obstructions | N/A | N/A | N/A |
| Distance to Furnace Flue | N/A | N/A | N/A |
| Spacing from Trees | 20 meters, NW | 20 meters, NW | 20 meters, NW |
| Nearest Major Roadway A | 27 th Ave | 27 th Ave | 27 th Ave |
| Distance and Direction to Road | 10 meters, E | 10 meters, E | 10 meters, E |
| Traffic Count (ADT) | 18,500 | 18,500 | 18,500 |
| Nearest Major Roadway B | I-10 | I-10 | I-10 |
| Distance and Direction to Road | 85 meters, N | 85 meters, N | 85 meters, N |
| Traffic Count (ADT) | 229,000 | 229,000 | 229,000 |
| Groundcover | Paved | Paved | Paved |

HIGLEY

County ID: HI

AQS ID: 04-013-4006

Address: 15400 South Higley Road, Gilbert

Coordinates: 33.31074N – 111.72255W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | |
|--|------------------------|
| Pollutant/Monitor Type | PM₁₀ |
| Sampling Schedule | Continuous |
| Analysis Method (filters only) | N/A |
| Any Proposal to Remove or Move Monitor? | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A |
| -Appendix A Requirements | |
| # Precision Checks Performed Annually | 24 |
| # Accuracy Checks Performed Annually | 2 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 |
| Frequency of One-Point QC Check | N/A |
| Frequency of Flow Rate Verification | Bi-Weekly |
| -Appendix C Requirements | |
| Sampler Make & Model | Thermo TEOM 1400AB |
| Date Established | 07/01/2000 |
| Classification | SLAMS |
| Method (FRM, FEM, ARM) | FEM |
| -Appendix D Requirements | |
| Monitoring Objective | Population Exposure |
| Monitoring Scale | Neighborhood |
| Sampling Season | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes |
| -Appendix E Requirements | |
| Distance between collocated samplers | N/A |
| Probe Inlet Height | 2.9 meters |
| Airflow Arc | 360° |
| Probe Sample Line Material | N/A |
| Pollutant Sample Residence Time | N/A |
| Distance from Supporting Structure | N/A |
| Distance from Obstructions | N/A |
| Distance to Furnace Flue | N/A |
| Spacing from Trees | N/A |
| Nearest Major Roadway A | Higley Rd |
| Distance and Direction to Road | 117 meters, E |
| Traffic Count (ADT) | 11,500 |
| Nearest Major Roadway B | Williams Field Rd |
| Distance and Direction to Road | 410 meters, S |
| Traffic Count (ADT) | 11,500 |
| Groundcover | Paved |

HUMBOLDT MOUNTAIN

County ID: HM

AQS ID: 04-013-9508

Address: Seven Springs Rd-FAA Radar Station, Tonto National Forest

Coordinates: 33.98280N – 111.79870W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | |
|--|--|
| Pollutant/Monitor Type | Ozone |
| Sampling Schedule | Continuous |
| Analysis Method (filters only) | N/A |
| Any Proposal to Remove or Move Monitor? | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A |
| -Appendix A Requirements | |
| # Precision Checks Performed Annually | 22 |
| # Accuracy Checks Performed Annually | 3 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly |
| Frequency of Flow Rate Verification | N/A |
| -Appendix C Requirements | |
| Sampler Make & Model | API M400 |
| Date Established | 01/01/1993 |
| Classification | SLAMS |
| Method (FRM, FEM, ARM) | FEM |
| -Appendix D Requirements | |
| Monitoring Objective | Max Ozone Concentration |
| Monitoring Scale | Regional |
| Sampling Season | Apr-Dec* |
| Network Meets Minimum Number of Monitors Required? | Yes |
| -Appendix E Requirements | |
| Distance between collocated samplers | N/A |
| Probe Inlet Height | 4.5 meters |
| Airflow Arc | 360° |
| Probe Sample Line Material | Teflon |
| Pollutant Sample Residence Time | 6.2 sec |
| Distance from Supporting Structure | N/A |
| Distance from Obstructions | N/A |
| Distance to Furnace Flue | N/A |
| Spacing from Trees | N/A |
| Nearest Major Roadway | N/A (Remote mountaintop site, only reachable by small access road) |
| Distance and Direction to Road | N/A |
| Traffic Count (ADT) | N/A |
| Groundcover | Dirt/Vegetated |

*Seasonal ozone monitors have been changed to year round operation in October 2010.

MESA
County ID: ME
AQS ID: 04-013-1003
Address: 310 S Brooks, Mesa
Coordinates: 33.41045N – 111.86507W
Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | | | |
|--|-----------------------|--------------------------|--------------------------|
| Pollutant/Monitor Type | CO | PM_{2.5} | PM₁₀ |
| Sampling Schedule | Continuous | 1 in 3 day | 1 in 6 day |
| Analysis Method (filters only) | N/A | Filters Weighed In-House | Filters Weighed In-house |
| Any Proposal to Remove or Move Monitor? | No | No | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A | Yes | N/A |
| -Appendix A Requirements | | | |
| # Precision Checks Performed Annually | 13 | N/A | N/A |
| # Accuracy Checks Performed Annually | 3 | 2 | 1 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes | Yes | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly | N/A | N/A |
| Frequency of Flow Rate Verification | N/A | Every 6 Weeks | Quarterly |
| -Appendix C Requirements | | | |
| Sampler Make & Model | API M400 | Thermo 2025 | Anderson SSI |
| Date Established | 01/01/1978 | 04/28/2005 | 01/23/1990 |
| Classification | SLAMS | SLAMS | SLAMS |
| Method (FRM, FEM, ARM) | FEM | FRM | FRM |
| -Appendix D Requirements | | | |
| Monitoring Objective | Population Exposure | Population Exposure | Population Exposure |
| Monitoring Scale | Neighborhood | Neighborhood | Neighborhood |
| Sampling Season | Sep-Mar | Jan-Dec | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes | Yes | Yes |
| -Appendix E Requirements | | | |
| Distance between collocated samplers | N/A | N/A | 3.3 meters |
| Probe Inlet Height | 7 meters | 6.9 meters | 6.2 meters |
| Airflow Arc | 360° | 360° | 360° |
| Probe Sample Line Material | Teflon | N/A | N/A |
| Pollutant Sample Residence Time | N/A | N/A | N/A |
| Distance from Supporting Structure | N/A | N/A | N/A |
| Distance from Obstructions | N/A | N/A | N/A |
| Distance to Furnace Flue | N/A | N/A | N/A |
| Spacing from Trees | N/A | N/A | N/A |
| Nearest Major Roadway | Broadway Rd. | Broadway Rd. | Broadway Rd. |
| Distance and Direction to Road | 305 meters, S | 305 meters, S | 305 meters, S |
| Traffic Count (ADT) | 33,000 | 33,000 | 33,000 |
| Groundcover | Paved/Gravel | Paved/Gravel | Paved/Gravel |

NORTH PHOENIX

County ID: NP

AQS ID: 04-013-1004

Address: 601 E Butler Dr., Phoenix

Coordinates: 33.56033N – 112.06626W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | | | |
|--|------------------------|------------------------|--------------------------|
| Pollutant/Monitor Type | Ozone | CO | PM₁₀ |
| Sampling Schedule | Continuous | Continuous | 1 in 6 day |
| Analysis Method (filters only) | N/A | N/A | Filters Weighed In-House |
| Any Proposal to Remove or Move Monitor? | No | No | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A | N/A | N/A |
| -Appendix A Requirements | | | |
| # Precision Checks Performed Annually | 25 | 16 | N/A |
| # Accuracy Checks Performed Annually | 5 | 1 | 1 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes | Yes | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly | Bi-Weekly | N/A |
| Frequency of Flow Rate Verification | N/A | N/A | Quarterly |
| -Appendix C Requirements | | | |
| Sampler Make & Model | API M400 | API M300 | Anderson SSI |
| Date Established | 01/01/1975 | 01/01/1974 | 01/05/1990 |
| Classification | SLAMS | SLAMS | SLAMS |
| Method (FRM, FEM, ARM) | FEM | FRM | FRM |
| -Appendix D Requirements | | | |
| Monitoring Objective | Population Exposure | Population Exposure | Population Exposure |
| Monitoring Scale | Neighborhood | Neighborhood | Neighborhood |
| Sampling Season | Jan-Dec | Sep-Mar | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes | Yes | Yes |
| -Appendix E Requirements | | | |
| Distance between collocated samplers | N/A | N/A | N/A |
| Probe Inlet Height | 4.6 meters | 4.6 meters | 4.4 meters |
| Airflow Arc | 360° | 360° | 360° |
| Probe Sample Line Material | Teflon | Teflon | N/A |
| Pollutant Sample Residence Time | 5.0 sec | N/A | N/A |
| Distance from Supporting Structure | N/A | N/A | N/A |
| Distance from Obstructions | N/A | N/A | N/A |
| Distance to Furnace Flue | N/A | N/A | N/A |
| Spacing from Trees | N/A | N/A | N/A |
| Nearest Major Roadway | 7 th Street | 7 th Street | 7 th Street |
| Distance and Direction to Road | 75 meters, E | 75 meters, E | 75 meters, E |
| Traffic Count (ADT) | 32,000 | 32,000 | 32,000 |
| Groundcover | Gravel | Gravel | Gravel |

PINNACLE PEAK

County ID: PP

AQS ID: 04-013-2005

Address: 25000 N Windy Walk, Scottsdale

Coordinates: 33.71231N – 111.85272W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | |
|--|-------------------------|
| Pollutant/Monitor Type | Ozone |
| Sampling Schedule | Continuous |
| Analysis Method (filters only) | N/A |
| Any Proposal to Remove or Move Monitor? | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A |
| -Appendix A Requirements | |
| # Precision Checks Performed Annually | 26 |
| # Accuracy Checks Performed Annually | 5 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly |
| Frequency of Flow Rate Verification | N/A |
| -Appendix C Requirements | |
| Sampler Make & Model | API M400 |
| Date Established | 02/01/1988 |
| Classification | SLAMS |
| Method (FRM, FEM, ARM) | FEM |
| -Appendix D Requirements | |
| Monitoring Objective | Max Ozone Concentration |
| Monitoring Scale | Urban |
| Sampling Season | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes |
| -Appendix E Requirements | |
| Distance between collocated samplers | N/A |
| Probe Inlet Height | 11.9 meters |
| Airflow Arc | 360° |
| Probe Sample Line Material | Teflon |
| Pollutant Sample Residence Time | 20.0 sec |
| Distance from Supporting Structure | N/A |
| Distance from Obstructions | N/A |
| Distance to Furnace Flue | N/A |
| Spacing from Trees | N/A |
| Nearest Major Roadway | Happy Valley Rd. |
| Distance and Direction to Road | 61 meters, S |
| Traffic Count (ADT) | 16,000 |
| Groundcover | Paved/Grass |

RIO VERDE

County ID: RV

AQS ID: 04-013-9706

Address: 25608 N Forest Rd., Rio Verde

Coordinates: 33.71881N – 111.67183W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | |
|--|-------------------------|
| Pollutant/Monitor Type | Ozone |
| Sampling Schedule | Continuous |
| Analysis Method (filters only) | N/A |
| Any Proposal to Remove or Move Monitor? | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A |
| -Appendix A Requirements | |
| # Precision Checks Performed Annually | 19 |
| # Accuracy Checks Performed Annually | 3 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly |
| Frequency of Flow Rate Verification | N/A |
| -Appendix C Requirements | |
| Sampler Make & Model | API M400 |
| Date Established | 01/01/1997 |
| Classification | SLAMS |
| Method (FRM, FEM, ARM) | FEM |
| -Appendix D Requirements | |
| Monitoring Objective | Max Ozone Concentration |
| Monitoring Scale | Urban |
| Sampling Season | Apr-Dec* |
| Network Meets Minimum Number of Monitors Required? | Yes |
| -Appendix E Requirements | |
| Distance between collocated samplers | N/A |
| Probe Inlet Height | 6.2 meters |
| Airflow Arc | 360° |
| Probe Sample Line Material | Teflon |
| Pollutant Sample Residence Time | 9.7 sec |
| Distance from Supporting Structure | N/A |
| Distance from Obstructions | N/A |
| Distance to Furnace Flue | N/A |
| Spacing from Trees | 16 meters, S |
| Nearest Major Roadway | Forest Rd |
| Distance and Direction to Road | 43 meters, E |
| Traffic Count (ADT) | Unknown |
| Groundcover | Paved |

*Seasonal ozone monitors have been changed to year round operation in October 2010.

SOUTH PHOENIX

County ID: SP

AQS ID: 04-013-4003

Address: 33 W Tamarisk, Phoenix

Coordinates: 33.40316N – 112.07533W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | | | | | |
|--|-----------------------|-----------------------|--------------------------|--------------------------|-----------------------|
| Pollutant/Monitor Type | Ozone | CO | PM _{2.5} | PM _{2.5} | PM ₁₀ |
| Sampling Schedule | Continuous | Continuous | 1 in 3 day | Continuous | Continuous |
| Analysis Method (filters only) | N/A | N/A | Filters Weighed In-House | N/A | N/A |
| Any Proposal to Remove or Move Monitor? | No | No | No | No | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A | N/A | Yes | Yes | N/A |
| -Appendix A Requirements | | | | | |
| # Precision Checks Performed Annually | 26 | 15 | N/A | 16 | 24 |
| # Accuracy Checks Performed Annually | 5 | 1 | 2 | 3 | 2 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes | Yes | Yes | Yes | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly | Bi-Weekly | N/A | N/A | N/A |
| Frequency of Flow Rate Verification | N/A | N/A | Every 6 Weeks | | Bi-Monthly |
| -Appendix C Requirements | | | | | |
| Sampler Make & Model | API M400 | API M300 | Thermo 2025 | Thermo FDMS-TEOM 1405-DF | Thermo TEOM 1400AB |
| Date Established | 10/01/1999 | 10/01/1999 | 01/01/2005 | 05/01/2010 | 7/1/2007 |
| Classification | SLAMS | SLAMS | SLAMS | SLAMS | SLAMS |
| Method (FRM, FEM, ARM) | FEM | FRM | FRM | FEM | FEM |
| -Appendix D Requirements | | | | | |
| Monitoring Objective | Population Exposure | Population Exposure | Population Exposure | Population Exposure | Population Exposure |
| Monitoring Scale | Neighborhood | Neighborhood | Neighborhood | Neighborhood | Neighborhood |
| Sampling Season | Jan-Dec | Sep-Mar | Jan-Dec | Jan-Dec | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes | Yes | Yes | Yes | Yes |
| -Appendix E Requirements | | | | | |
| Distance between collocated samplers | N/A | N/A | N/A | N/A | N/A |
| Probe Inlet Height | 4.9 meters | 4.9 meters | 5.5 meters | 5.5 meters | 5.4 meters |
| Airflow Arc | 360° | 360° | 360° | 360° | 360° |
| Probe Sample Line Material | Teflon | Teflon | N/A | N/A | N/A |
| Pollutant Sample Residence Time | 6.9 sec | N/A | N/A | N/A | N/A |
| Distance from Supporting Structure | N/A | N/A | N/A | N/A | N/A |
| Distance from Obstructions | N/A | N/A | N/A | N/A | N/A |
| Distance to Furnace Flue | N/A | N/A | N/A | N/A | N/A |
| Spacing from Trees | N/A | N/A | N/A | N/A | N/A |
| Nearest Major Roadway A | Central Ave | Central Ave | Central Ave | Central Ave | Central Ave |
| Distance and Direction to Road | 168 meters, E | 168 meters, E | 168 meters, E | 168 meters, E | 165 meters, E |
| Traffic Count (ADT) | 24,000 | 24,000 | 24,000 | 24,000 | 24,000 |
| Nearest Major Roadway B | Broadway Rd | Broadway Rd | Broadway Rd | Broadway Rd | Broadway Rd |
| Distance and Direction to Road | 385 meters, N | 385 meters, N | 385 meters, N | 385 meters, N | 385 meters, N |
| Traffic Count (ADT) | 18,000 | 18,000 | 18,000 | 18,000 | 13,000 |
| Groundcover | Paved | Paved | Paved | Paved | Paved |

*Unavailable at time of publication

SOUTH SCOTTSDALE

County ID: SS

AQS ID: 04-013-3003

Address: 2857 N Miller Rd., Scottsdale

Coordinates: 33.47968N – 111.91721W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | | | | | |
|--|-----------------------|-----------------------|-----------------------|-----------------------|--------------------------|
| Pollutant/Monitor Type | Ozone | CO | NO ₂ | SO ₂ | PM ₁₀ |
| Sampling Schedule | Continuous | Continuous | Continuous | Continuous | 1 in 6 day |
| Analysis Method (filters only) | N/A | N/A | N/A | N/A | Filters Weighed In-House |
| Any Proposal to Remove or Move Monitor? | No | No | No | No | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A | N/A | N/A | N/A | N/A |
| -Appendix A Requirements | | | | | |
| # Precision Checks Performed Annually | 26 | 15 | 27 | 26 | 60 (Collocated) |
| # Accuracy Checks Performed Annually | 4 | 2 | 4 | 5 | 1 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes | Yes | Yes | Yes | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly | Bi-Weekly | Bi-Weekly | Bi-Weekly | N/A |
| Frequency of Flow Rate Verification | N/A | N/A | N/A | N/A | Quarterly |
| -Appendix C Requirements | | | | | |
| Sampler Make & Model | API M400 | API M300 | API M200 | API M100 | Anderson SSI |
| Date Established | 01/01/1974 | 01/01/1974 | 10/01/1975 | 01/01/1984 | 07/01/1987 |
| Classification | SLAMS | SLAMS | SLAMS | SLAMS | SLAMS |
| Method (FRM, FEM, ARM) | FEM | FRM | FRM | FEM | FRM |
| -Appendix D Requirements | | | | | |
| Monitoring Objective | Population Exposure | Population Exposure | Population Exposure | Population Exposure | Population Exposure |
| Monitoring Scale | Neighborhood | Neighborhood | Urban | Neighborhood | Neighborhood |
| Sampling Season | Jan-Dec | Sep-Mar | Jan-Dec | Jan-Dec | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes | Yes | Yes | Yes | Yes |
| -Appendix E Requirements | | | | | |
| Distance between collocated samplers | N/A | N/A | N/A | N/A | 6.5 meters |
| Probe Inlet Height | 5.8 meters | 5.8 meters | 5.8 meters | 5.8 meters | 5.1 meters |
| Airflow Arc | 360° | 360° | 360° | 360° | 360° |
| Probe Sample Line Material | Teflon | Teflon | Teflon | Teflon | N/A |
| Pollutant Sample Residence Time | 11.1 sec | N/A | 11.1 sec | 12.1 sec | N/A |
| Distance from Supporting Structure | N/A | N/A | N/A | N/A | N/A |
| Distance from Obstructions | N/A | N/A | N/A | N/A | N/A |
| Distance to Furnace Flue | N/A | N/A | N/A | N/A | N/A |
| Spacing from Trees | 14 meters, S | 14 meters, S | 14 meters, S | 14 meters, S | 14 meters, S |
| Nearest Major Roadway A | Thomas | Thomas | Thomas | Thomas | Thomas |
| Distance and Direction to Road | 66 meters, N | 66 meters, N | 66 meters, N | 66 meters, N | 62 meters, N |
| Traffic Count (ADT) | 33,000 | 33,000 | 33,000 | 33,000 | 33,000 |
| Nearest Major Roadway B | Miller | Miller | Miller | Miller | Miller |
| Distance and Direction to Road | 32 meters, W | 32 meters, W | 32 meters, W | 32 meters, W | 35 meters, W |
| Traffic Count (ADT) | 13,000 | 13,000 | 13,000 | 13,000 | 13,000 |
| Groundcover | Paved | Paved | Paved | Paved | Paved |

TEMPE

County ID: TE

AQS ID: 04-013-4005

Address: 1525 S College, Tempe

Coordinates: 33.4124N – 111.93473W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | | |
|--|----------------------------|----------------------------|
| Pollutant/Monitor Type | Ozone | CO |
| Sampling Schedule | Continuous | Continuous |
| Analysis Method (filters only) | N/A | N/A |
| Any Proposal to Remove or Move Monitor? | No | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A | N/A |
| -Appendix A Requirements | | |
| # Precision Checks Performed Annually | 22 | 14 |
| # Accuracy Checks Performed Annually | 3 | 3 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly | Bi-Weekly |
| Frequency of Flow Rate Verification | N/A | N/A |
| -Appendix C Requirements | | |
| Sampler Make & Model | API M400 | API M300 |
| Date Established | 07/01/2000 | 07/01/2000 |
| Classification | SLAMS | SLAMS |
| Method (FRM, FEM, ARM) | FEM | FRM |
| -Appendix D Requirements | | |
| Monitoring Objective | Population Exposure | Population Exposure |
| Monitoring Scale | Neighborhood | Neighborhood |
| Sampling Season | Jan-Dec | Sep-Mar |
| Network Meets Minimum Number of Monitors Required? | Yes | Yes |
| -Appendix E Requirements | | |
| Distance between collocated samplers | N/A | N/A |
| Probe Inlet Height | 4.4 meters | 4.4 meters |
| Airflow Arc | 360° | 360° |
| Probe Sample Line Material | Teflon | Teflon |
| Pollutant Sample Residence Time | 5.4 sec | N/A |
| Distance from Supporting Structure | N/A | N/A |
| Distance from Obstructions | N/A | N/A |
| Distance to Furnace Flue | N/A | N/A |
| Spacing from Trees | N/A | N/A |
| Nearest Major Roadway A | College Ave | College Ave |
| Distance and Direction to Road | 11 meters, W | 11 meters, W |
| Traffic Count (ADT) | Unknown (secondary street) | Unknown (secondary street) |
| Nearest Major Roadway B | Apache | Apache |
| Distance and Direction to Road | 370 meters, N | 370 meters, N |
| Traffic Count (ADT) | 25000 | 25000 |
| Groundcover | Gravel | Gravel |

WEST CHANDLER

County ID: WC

AQS ID: 04-013-4004

Address: 275 S Ellis, Chandler

Coordinates: 33.29898N – 111.88431W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | | | |
|--|----------------------------|----------------------------|----------------------------|
| Pollutant/Monitor Type | Ozone | CO | PM₁₀ |
| Sampling Schedule | Continuous | Continuous | Continuous |
| Analysis Method (filters only) | N/A | N/A | N/A |
| Any Proposal to Remove or Move Monitor? | No | No | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A | N/A | N/A |
| -Appendix A Requirements | | | |
| # Precision Checks Performed Annually | 22 | 15 | 24 |
| # Accuracy Checks Performed Annually | 4 | 1 | 2 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes | Yes | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly | Bi-Weekly | N/A |
| Frequency of Flow Rate Verification | N/A | N/A | Monthly |
| -Appendix C Requirements | | | |
| Sampler Make & Model | API M400 | API M300 | Anderson SSI |
| Date Established | 07/01/2000 | 07/01/2000 | 07/01/2000 |
| Classification | SLAMS | SLAMS | SLAMS |
| Method (FRM, FEM, ARM) | FEM | FRM | FRM |
| -Appendix D Requirements | | | |
| Monitoring Objective | Population Exposure | Population Exposure | Population Exposure |
| Monitoring Scale | Neighborhood | Neighborhood | Middle |
| Sampling Season | Apr-Dec* | Sep-Mar | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes | Yes | Yes |
| -Appendix E Requirements | | | |
| Distance between collocated samplers | N/A | N/A | N/A |
| Probe Inlet Height | 4.4 meters | 4.4 meters | 4.4 meters |
| Airflow Arc | 360° | 360° | 360° |
| Probe Sample Line Material | Teflon | Teflon | N/A |
| Pollutant Sample Residence Time | 4.6 sec | N/A | N/A |
| Distance from Supporting Structure | N/A | N/A | N/A |
| Distance from Obstructions | N/A | N/A | N/A |
| Distance to Furnace Flue | N/A | N/A | N/A |
| Spacing from Trees | 14 meters, E | 14 meters, E | 14 meters, E |
| Nearest Major Roadway A | Frye Rd | Frye Rd | Frye Rd |
| Distance and Direction to Road | 23 meters, S | 23 meters, S | 25 meters, S |
| Traffic Count (ADT) | Unknown (secondary street) | Unknown (secondary street) | Unknown (secondary street) |
| Nearest Major Roadway B | Ellis St | Ellis St | Ellis St |
| Distance and Direction to Road | 73 meters, W | 73 meters, W | 71 meters, W |
| Traffic Count (ADT) | Unknown (secondary street) | Unknown (secondary street) | Unknown (secondary street) |
| Groundcover | Paved/Gravel | Paved/Gravel | Paved/Gravel |

*Seasonal ozone monitors have been changed to year round operation in October 2010.

WEST 43RD AVENUE

County ID: WF

AQS ID: 04-013-4009

Address: 3940 W Broadway, Phoenix

Coordinates: 33.40642N – 112.14434W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | |
|--|------------------------|
| Pollutant/Monitor Type | PM₁₀ |
| Sampling Schedule | Continuous |
| Analysis Method (filters only) | N/A |
| Any Proposal to Remove or Move Monitor? | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A |
| -Appendix A Requirements | |
| # Precision Checks Performed Annually | 26 |
| # Accuracy Checks Performed Annually | 1 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 |
| Frequency of One-Point QC Check | N/A |
| Frequency of Flow Rate Verification | Bi-Weekly |
| -Appendix C Requirements | |
| Sampler Make & Model | Thermo TEOM 1400AB |
| Date Established | 04/01/2002 |
| Classification | SLAMS |
| Method (FRM, FEM, ARM) | FEM |
| -Appendix D Requirements | |
| Monitoring Objective | Highest Concentrations |
| Monitoring Scale | Middle |
| Sampling Season | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes |
| -Appendix E Requirements | |
| Distance between collocated samplers | N/A |
| Probe Inlet Height | 5 meters |
| Airflow Arc | 360° |
| Probe Sample Line Material | N/A |
| Pollutant Sample Residence Time | N/A |
| Distance from Supporting Structure | N/A |
| Distance from Obstructions | N/A |
| Distance to Furnace Flue | N/A |
| Spacing from Trees | N/A |
| Nearest Major Roadway | Broadway Road |
| Distance and Direction to Road | 37 meters, SE |
| Traffic Count (ADT) | Unknown |
| Groundcover | Gravel |

WEST INDIAN SCHOOL ROAD

County ID: WI

AQS ID: 04-013-0016

Address: 3315 W Indian School Rd, Phoenix

Coordinates: 33.49462N – 112.13095W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | |
|--|---|
| Pollutant/Monitor Type | CO |
| Sampling Schedule | Continuous |
| Analysis Method (filters only) | N/A |
| Any Proposal to Remove or Move Monitor? | Yes, site closed June 2010 |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A |
| -Appendix A Requirements | |
| # Precision Checks Performed Annually | 13 |
| # Accuracy Checks Performed Annually | 2 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly |
| Frequency of Flow Rate Verification | N/A |
| -Appendix C Requirements | |
| Sampler Make & Model | API M300 |
| Date Established | 12/01/1980 |
| Classification | SLAMS |
| Method (FRM, FEM, ARM) | FRM |
| -Appendix D Requirements | |
| Monitoring Objective | Highest Concentration |
| Monitoring Scale | Micro-scale |
| Sampling Season | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes |
| -Appendix E Requirements | |
| Distance between collocated samplers | N/A |
| Probe Inlet Height | 2.6 meters |
| Airflow Arc | 360° |
| Probe Sample Line Material | Teflon |
| Pollutant Sample Residence Time | N/A |
| Distance from Supporting Structure | 2 meters from side of building |
| Distance from Obstructions | Roofline 2 meters to South, .5 meters above probe |
| Distance to Furnace Flue | N/A |
| Spacing from Trees | N/A |
| Nearest Major Roadway | Indian School Road |
| Distance and Direction to Road | 3 meters, N |
| Traffic Count (ADT) | 50,000 |
| Groundcover | Paved |

WEST PHOENIX

County ID: WP

AQS ID: 04-013-0019

Address: 3847 W Earll, Phoenix

Coordinates: 33.48385N – 112.14257W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | | | | | | |
|--|-----------------------|-----------------------|-----------------------|---------------------------------|-------------------------------|--------------------------|
| Pollutant/Monitor Type | Ozone | CO | NO₂ | PM_{2.5} | PM_{2.5} | PM₁₀ |
| Sampling Schedule | Continuous | Continuous | Continuous | 1 in 3 days | Continuous | Continuous |
| Analysis Method (filters only) | N/A | N/A | N/A | Filters Weighed In- House | N/A | N/A |
| Any Proposal to Remove or Move Monitor? | No | No | No | No | No | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A | N/A | N/A | Yes | Yes | N/A |
| -Appendix A Requirements | | | | | | |
| # Precision Checks Performed Annually | 25 | 26 | 25 | 28 (Collocated) | 18 | 23 |
| # Accuracy Checks Performed Annually | 5 | 4 | 5 | 2 | 1 | 2 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes | Yes | Yes | Yes | Yes | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 | Pending for July 2011 |
| Frequency of One-Point QC Check | Bi-Weekly | Bi-Weekly | Bi-Weekly | N/A | N/A | N/A |
| Frequency of Flow Rate Verification | N/A | N/A | N/A | Every 6 weeks | Bi-Weekly | Bi-Weekly |
| -Appendix C Requirements | | | | | | |
| Sampler Make & Model | API M400 | API M300 | API M200 | Thermo 2025 | Thermo FDMS-TEOM 1400AB | Thermo TEOM 1400AB |
| Date Established | 01/01/84 | 01/01/84 | 05/24/90 | 06/13/00 | 09/01/05 | 02/01/88 |
| Classification | SLAMS | SLAMS | SLAMS | SLAMS | SLAMS | SLAMS |
| Method (FRM, FEM, ARM) | FEM | FRM | FRM | FRM | None | FEM |
| -Appendix D Requirements | | | | | | |
| Monitoring Objective | Population Exposure | Population Exposure | Population Exposure | Highest Concentration | Highest Concentration | Population Exposure |
| Monitoring Scale | Neighborhood | Neighborhood | Neighborhood | Neighborhood | Neighborhood | Neighborhood |
| Sampling Season | Jan-Dec | Jan-Dec | Jan-Dec | Jan-Dec | Jan-Dec | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes | Yes | Yes | Yes | Yes | Yes |
| -Appendix E Requirements | | | | | | |
| Distance between collocated samplers | N/A | N/A | N/A | 2.3 meters | N/A | N/A |
| Probe Inlet Height | 4.3 meters | 4.3 meters | 4.3 meters | 2.8 meter | 3.6 meter | 2.7 meters |
| Airflow Arc | 360° | 360° | 360° | 360° | 360° | 360° |
| Probe Sample Line Material | Teflon | Teflon | Teflon | N/A | N/A | N/A |
| Pollutant Sample Residence Time | 4.4 sec | N/A | 4.4 sec | N/A | N/A | N/A |
| Distance from Supporting Structure | N/A | N/A | N/A | N/A | N/A | N/A |
| Distance from Obstructions | N/A | N/A | N/A | N/A | N/A | N/A |
| Distance to Furnace Flue | N/A | N/A | N/A | N/A | N/A | N/A |
| Spacing from Trees | N/A | N/A | N/A | N/A | N/A | N/A |
| Nearest Major Roadway | Thomas | Thomas | Thomas | Thomas | Thomas | Thomas |
| Distance and Direction to Road | 360 meters, S | 360 meters, S | 360 meters, S | 360 meters, S | 360 meters, S | 360 meters, S |
| Traffic Count (ADT) | 29,000 | 29,000 | 29,000 | 29,000 | 29,000 | 29,000 |
| Groundcover | Gravel | Gravel | Gravel | Gravel | Gravel | Gravel |

ZUNI HILLS

County ID: ZH

AQS ID: 04-013-4016

Address: 10851 West Williams Rd., Sun City, AZ

Coordinates: 33.68674N, -112.29417W

Metropolitan Sampling Area (MSA): 6200 Phoenix-Mesa

| -General Information | |
|--|------------------------------|
| Pollutant/Monitor Type | PM₁₀ |
| Sampling Schedule | Continuous |
| Analysis Method (filters only) | N/A |
| Any Proposal to Remove or Move Monitor? | No |
| Is site suitable for comparison to PM _{2.5} NAAQS per Part 58.30? | N/A |
| -Appendix A Requirements | |
| # Precision Checks Performed Annually | 23 |
| # Accuracy Checks Performed Annually | 2 |
| All Precision/Accuracy Reports Submitted to AQS? | Yes |
| Annual Data Certification Submitted? | Pending for July 2011 |
| Frequency of One-Point QC Check | N/A |
| Frequency of Flow Rate Verification | Bi-Weekly |
| -Appendix C Requirements | |
| Sampler Make & Model | Thermo TEOM 1400AB |
| Date Established | 12/01/09 |
| Classification | SLAMS |
| Method (FRM, FEM, ARM) | FEM |
| -Appendix D Requirements | |
| Monitoring Objective | Population Exposure |
| Monitoring Scale | Neighborhood Scale |
| Sampling Season | Jan-Dec |
| Network Meets Minimum Number of Monitors Required? | Yes |
| -Appendix E Requirements | |
| Distance between collocated samplers | N/A |
| Probe Inlet Height | 2.3 meters |
| Airflow Arc | 360° |
| Probe Sample Line Material | N/A |
| Pollutant Sample Residence Time | N/A |
| Distance from Supporting Structure | N/A |
| Distance from Obstructions | N/A |
| Distance to Furnace Flue | N/A |
| Spacing from Trees | N/A |
| Nearest Major Roadway | Williams Rd |
| Distance and Direction to Road | 200 meters, N |
| Traffic Count (ADT) | Unknown (residential street) |
| Groundcover | Lawn/Dirt |

**APPENDIX III - PUBLIC NOTICE AND COMMENT
INFORMATION**

Public Notice Period

To fulfill the requirements of 40CFR58 §58.10, the Maricopa County Air Quality Department posted a draft copy of this Network Review on its website on <Date>. In an effort to notify the public of this network review, the department published information on a Network Review Public Workshop through the following outlets:

- News item on department website.
- Electronic feed to subscribers.
- Public Notice posted in the Arizona Republic, a newspaper of general circulation in Maricopa County.

News Release

The following is a copy of the news release that was advertised in the Arizona Republic:

Public Notice

The Maricopa County Air Quality Department will hold a public meeting to discuss its 2010 Air Monitoring Network Review on <Date>. The meeting will be held at the Air Monitoring Division's offices at 2145 S. 11th Ave. suite 170, Phoenix, AZ 85007.

A copy of the draft network review is currently available on the department's website at the following website address:

<http://www.maricopa.gov/aq/divisions/monitoring/network.aspx>

Hard copies of the document may be requested from the department's Records Management Coordinator at (602) 506-6201 or at the department's address: 1001 North Central Avenue, Phoenix, Arizona 85004. Arrangements may be made to view the information every Monday through Friday (excluding major holidays) between 8:00 a.m. and 4:30 p.m. There is a small fee for copying available documents.

The 2010 Air Monitoring Network Review covers ambient air monitoring activity captured by the department's 25 air monitoring sites throughout 2010. The Air Monitoring Network Review also provides a summary of the pollutants measured by Maricopa County, a look at the air monitoring network design and monitoring site details and statistics from the past year among other information. Additional information on the draft Air Monitoring Network Review may be obtained by contacting Ben Davis at 2145 S 11th Avenue #170, Phoenix, AZ 85007 or (602) 258-5155 x221.

The purpose of <Date> public meeting is to receive comments from the public on the draft Network Review. Members of the public may comment in person or through written statements to the department.

Written comments shall state the name and mailing address of the person making comment and be signed by that person or authorized agent or attorney. Written comments on the draft document are due to the department by <Date> at 5:00 p.m.

A sign language and/or Spanish interpreter will be made available upon request with 72 hours notice. Additional reasonable accommodations will be made available to the extent possible within the time frame of the request.

Dates of Publication:

Arizona Republic: <Date>.

Public Comments

<Awaiting Comments>